

TECHNICAL INFORMATION

Cleaner



Gentle cleaning with the LOBA system




Highly concentrated, pH neutral cleaner. Quick cleaning, dries without streaks. Its surface-protecting and extremely extensive cleaning performance make it a universal product.

- Excellent cleaning effect thanks to superb dirt-dissolving power
- Extremely economical concentrated, 1 litre of LOBACARE® Cleaner yields up to 200 litres of ready-to-use cleaning solution
- Material-protecting and pH-neutral
- Can be used universally for all waterproof surfaces
- Environmentally friendly biodegradable cleaner

Range of use:

Suitable for cleaning all water-resistant surfaces such as hardwood floors, cork coverings, linoleum, PVC, stone flooring and other floor coverings. Also suitable for cleaning doors, tiles, walls, window frames, glass and plastic surfaces.

Technical Data

Art.-no. 10175			
	1 l	12	480
	10 l	-	60
	250 ml	12	-
Solids	12 ±2%		
pH	6.5		
Contents	5 - 15% anionic surfactants, perfumes, LINALOOL, BUTYLPHENYL METHYLPROPIONAL, METHYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE		
Storage and transportation	36 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.		
GISCODE	GU70		

Application

- Shake the contents well.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at www.wingis-online.de.

Thinner

Water.



TECHNICAL INFORMATION

Cleaner



Application

Application tool/application rate

LOBATOOL mop. On large areas, use a suitable flat wiper mop, Marob-Gigant or a scourer-vacuum machine. / Depending on the application, add approx. 50 - 100ml to a bucket with 10 l of water, sufficient for 100 m².

Application:

Mix the cleaning concentrate with water, using a higher ratio for heavier soiling. Damp-wipe the surface with cleaning solution using a suitable cleaning device.

Using too much water and allowing the product to work for too long can cause swelling of parquet and cork flooring and must therefore be avoided.

The product is also suitable for use in scourer-vacuum machines. To avoid excess foaming in the dirty water tank, we recommend adding LOBACARE[®] Entschäumer (defoamer).

General guidelines

Cleaning of tools: Clean tools and equipment immediately with water.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

Drying time: The indicated drying times are valid for +20°C and 55% to 65% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

The words or symbols denoted by [®] stand for trademark rights that are at least registered and protected in the territory of Germany.

