

WAKOL R 4515 Tile cleaner

Technical Information

Area of application

Cleaner for manual or machine application on old tiled floors for removal of layers of old care products and extreme dirt before subsequent tile laying.

Technical data

Raw material base:	anionic and nonionic tensides
Mixing ratio:	1:3
Consumption:	approx. 1,0 l WAKOL R 4515 / 20 m ²
pH – value:	10,2
Storage temperature:	not below +5 °C, sensitive to frost
Storage time:	approx. 36 months in tightly sealed container
Marking according to Ordinance on Hazardous Substances:	see safety data sheet
GISCODE:	GG60

Usage

Spread the tile cleaner over the floor with the single-disc machine and a black pad, finish the edges manually, leave for at least 10 mins and then again treat the surface with black pad or cleaning brushes. Then soak up the cleaning fluid e.g. with a wet-suction device, do not allow to dry. Neutralise residues by cleaning again twice with clear water and allow the surface to dry before carrying out further work.

Important

Processing not below floor temperature of +15 °C and room temperature of +18 °C, as well as room humidity preferably between 40 % and 65 %, maximum 75 %.
In cold weather, warm up WAKOL R 4515 Tile cleaner in due time in heated room.

All information is based on approx. 20 °C and 65 % relative air humidity.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.
This Technical Information of 29.08.2016 supersedes all previous versions.

Wakol GmbH
Bottenbacher Straße 30
D-66954
Pirmasens
Tel. +49 6331 8001 131
Fax +49 6331 8001 890
www.wakol.com



Wakol GmbH
Industriestraße 5
A-6841
Mäder
Tel. +43 5523 64 700
Fax +43 5523 64 700 64
www.wakol.at

Wakol Adhesa AG/SA
Schützengasse 28
CH-9410
Heiden
Tel. +41 31 9210 755
Fax +41 31 9212 968
www.wakoladhesa.ch

Wakol Foreco srl
Via Kennedy 75
I-20010
Marcallo con Casone
Tel. +39 02 9761 939
Fax +39 02 97 253 021
www.wakolforeco.it

Loba-Wakol Polska Sp.z o.o.
ul. Sławęcińska 16, Macierzysz
PL-05-850
Ożarów Mazowiecki
Tel. +48 22 436 24 20
Fax +48 22 436 24 21
www.loba-wakol.pl

Lecol Chemie B.V.
Schutweg 6
NL-5145 NP
Waalwijk
Tel. +31 416 566 540
Fax +31 416 566 531
www.lecol.nl