

EVERY WOODEN FLOOR DESERVES THE VERY BEST.



VERSION 02.2024

lecol[®]

EVERY WOODEN FLOOR DESERVES THE VERY BEST.

EVERYTHING YOU NEED FOR PROFESSIONAL INSTALLATION, FINISHING, RENOVATION AND MAINTENANCE OF WOODEN FLOORS & PARQUET.

Lecol has over 50 years of experience in The Netherlands, Belgium and United Kingdom. We help professionals in the wooden flooring industry to achieve great standards with our high quality products, advice, knowledge and expertise. Whatever your job or type of wooden floor covering is, from pre-treatment, levelling, sanding and gluing to oiling or lacquering and maintenance, we offer a unique and complete system that is a suitable solution for every situation and all wooden floor types.

All of our products work together to offer connected systems that are produced and developed in Germany by WAKOL and LOBA. Like the members of a relay team, each member has a complementary and strengthening effect on each other. Combined with our personal and technical project support (including site visits by appointment), we will help you achieve a perfectly finished floor. We will always look to provide helpful advice and action. No problem is too big, no questions are too ridiculous. We help professionals. No matter what.



PERSONAL

We are happy to be contacted directly and speak your language as a professional.



POWERFUL

What we give you is security. We stand by our products and offer you active project support.



SKILLED

We are highly experienced in the field of floor preparation, installation, renovation, finishing and maintenance.





HIGH QUALITY PRODUCTS. AWESOME SERVICE.

—
**LECOL PROVIDES THE ASSURANCE THAT YOUR
PROJECT WILL GO TO PLAN.**

With our great range of quality products Lecol aims to provide a smooth and reliable realisation of your project.

Our active project support and in-depth knowledge of techniques, products (together they offer connected systems) and applications can contribute to the best possible result. As a customer you will be supported with practical solutions. We are committed to supporting you both personally and technically. If you need an onsite demonstration, you can make an appointment with our representatives and we will show you the best way to work with our products and share our knowledge with your team. Contact us and we will help you!

lecol^R

LOBA – WAKOL CONNECTED SYSTEMS.

Top performances need top products that are perfectly matched to each other. With Connected Systems, we offer a solution that represents a guaranteed best possible result. Below we would like to explain why our connected systems offer the assurances you need.



LOBA

LOBA is a German producer of systems to finish and maintain wooden and cork floors. Product Categories include water based lacquers and primers, oil based finishes, colouring systems, maintenance products and application tools.

Well known products include LOBA 2K InvisibleProtect, LOBA EasyPrime, LOBA Viva, LOBA 2K Fusion, LOBA 2K Supra A.T. and LOBA 2K ImpactOil.

WAKOL

Wakol is a German producer of systems for the installation of wooden and cork floors. Product Categories include adhesives, primers, levellers and repair products. Well known products include WAKOL Z 520 Thin Screed, WAKOL PU 280 Polyurethane primer/DPM, WAKOL MS 330 Silane primer/DPM, WAKOL MS 260 hard Elastic parquet & cork adhesive.

These two producers have worked together for more than 20 years and now they combined forces.

WHAT DOES LOBA-WAKOL STAND FOR

- The products of WAKOL and LOBA are designed to be used in conjunction
- This ensures the maximum security during processing
- Chemical reactions between the lacquer/oil and the adhesive are prevented
- Dark joints will be prevented
- It is a guaranteed system using products that are continually tested and verified

HELP AND ADVICE

If you need help and advice on something that is not covered, please contact us and we will try our best to answer your questions.



LOBA AND WAKOL CONNECTED SYSTEMS FOR ADHESIVES AND OILS.



CONNECTED SYSTEMS

WAKOL																
1K PARQUET ADHESIVE											2K PARQUET ADHESIVE					
D 1640	D 1690	MS 228	MS 230	MS 232	MS 260	MS 261	MS 262	MS 265	MS 290	MS 292	PU 385	PU 210	PU 215	PU 216	PU 220	PU 225

LOBA	OIL	2K IMPACTOIL
		2K IMPACTOIL COLOR
		AKZENT 100 OIL
		HARDWAXOIL ECOPLUS
		MARKANT
		MARKANTCOLOR
		MARKANTNATURE

•	•	•	•	•	•	•	•	•	•	•	•					
•	•	•	•	•	•	•	•	•	•	•	•					
•	•				•	•	•	•	•	•	•					
•	•						•	•	•	•	•					
•	•							•	•	•	•	•	•	•	•	•
•	•								•	•	•	•	•	•	•	•
•	•							•	•	•	•	•	•	•	•	•

•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•

LOBA AND WAKOL CONNECTED SYSTEMS FOR ADHESIVES AND LACQUERS.



CONNECTED SYSTEMS

WAKOL																
1K PARQUET ADHESIVE											2K PARQUET ADHESIVE					
D 1640	D 1690	MS 228	MS 230	MS 232	MS 260	MS 261	MS 262	MS 265	MS 290	MS 292	PU 385	PU 210	PU 215	PU 216	PU 220	PU 225

LOBA	1K FINISH	EASYFINISH
		VIVA
		LIFE

•	•				•	•	•	•	•	•	•					
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

•	•	•	•	•
•	•	•	•	•
•	•	•	•	•

LOBA	2K FINISH	INVISIBLEPROTECT
		SUPRA
		DUO
		FUSION
		RUSH

•	•	•	•	•	•	•	•	•	•	•	•					
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
•	•				•	•	•	•	•	•	•	•	•	•	•	•
•	•				•	•	•	•	•	•	•	•	•	•	•	•

•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•
•	•	•	•	•

PRODUCTS THAT SCORE WELL FOR SUSTAINABILITY.

Wakol is a German producer of systems for the installation of wooden and cork floors. Product Categories include adhesives, primers, levellers and repair products. Well known products include WAKOL Z 520 Thin Screed, WAKOL PU 280 Polyurethane primer/DPM, WAKOL MS 330 Silane primer/DPM, WAKOL MS 260 hard Elastic parquet & cork adhesive.

IMPORTANT ENVIRONMENTAL CHARACTERISTICS

- EMICODE EC1 Plus, very low emission (almost every product)
- Blauer Engel, very low emission (most of the products)
- BREEAM and LEED compliant regarding Volatile Organic Compounds (VOC)
- Water-based fillers
- Solvent-free oil, 100% natural raw materials
- Water-based parquet lacquer, VOC content well below current standard
- 100% solvent-free maintenance products
















INDEX.

PRIMERS	PAG. 5	FILLERS	PAG. 13
LEVELLING COMPOUNDS	PAG. 6	LACQUERS	PAG. 14-16
MS ADHESIVES FOR SOLID		SOLVENT COLOURS	PAG. 17
WOOD & PARQUET FLOORS	PAG. 7	SOLVENT BASED ADHESIVES FOR SOLID	
PU ADHESIVES FOR SOLID		WOOD & PARQUET FLOORS	PAG. 19
WOOD & PARQUET FLOORS	PAG. 8	HARD WAX OIL & COLOUR	PAG. 21
WATER BASED ADHESIVES FOR SOLID		OIL & COLOURS	PAG. 23-24
WOOD, CORK & PARQUET FLOORS	PAG. 9	MAINTENANCE PRODUCTS	PAG. 25-26
FLOW CHART INSTALLATION	PAG. 11	INSTALLATION ACCESSORIES /	
		ANCILIARIES	PAG. 27-28

















PRIMERS

PRODUCT	ARTICLE NUMBER / CONTENT	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
WAKOL D 3003 DISPERSION PRIMER 	<ul style="list-style-type: none"> • 165901 - 10 KG 	<ul style="list-style-type: none"> • Self levelling compound primer for absorbent subfloors • Waterbased • Ready-to-use 	<p>DRYING TIME: on cement screeds/ concrete following visible drying; calcium sulphate screed & gypsum fibre boards at least 60 minutes; cast asphalt & water-resistant adhesive residues after approx. 30-60 minutes</p>	90-140 g	
WAKOL D 3045 SPECIAL PRIMER 	<ul style="list-style-type: none"> • 167878 - 6 KG • 125113 - 12 KG 	<ul style="list-style-type: none"> • Self levelling compound primer for non-absorbent subfloors like tiles and as an adhesive bridge for Wakol levelling compounds on WAKOL PU280 Polyurethane Primer or WAKOL MS330 Silane Primer • Waterbased • Ready-to-use 	<p>DRYING TIME: approx. 30-60 minutes, approx. 60-120 minutes on wooden sheet material</p>	100-150 g	
WAKOL D 3055 PARQUET PRIMER 	<ul style="list-style-type: none"> • 135008 - 10 KG 	<ul style="list-style-type: none"> • Waterbased primer for under Wood-en flooring adhesives on absorbant subfloors • Quick drying • Not suitable as damp proof membrane • Non hazardous 	<p>DRYING TIME: on cement screeds following visible drying approx. 30 minutes, on calcium sulphate concrete and gypsum fibre boards after approx. 2 hours</p>	100-150 g	
WAKOL PU 280 POLYURETHANE PRIMER / DPM 	<ul style="list-style-type: none"> • 124166 - 5 KG • 122289 - 11 KG 	<ul style="list-style-type: none"> • Quick drying (dry in only 45 min.) • Single component polyurethane resin primer • Suitable for use as a DPM • Strengthens the subfloor • Can be used on absorbent and non-absorbent subfloors • Solvent and water free 	<p>DRYING TIME: approx. 40-50 minutes</p>	<p>approx. 100-150 g/m² as primer, approx. 250-350 g/m² as moisture barrier</p>	 
WAKOL MS 330 SILANE PRIMER / DPM 	<ul style="list-style-type: none"> • 167877 - 5 KG • 147515 - 10 KG 	<ul style="list-style-type: none"> • Quick drying (dry in only 60 min.) • Single component silane primer • One coat only DPM • Strengthens the subfloor • Can be used on absorbent and non-absorbent subfloors • Solvent and water free 	<p>DRYING TIME: approx. 60 minutes</p>	<p>approx. 80-120 g/m² as primer, approx. 250 g/m² as moisture barrier</p>	

LEVELLING COMPOUNDS

PRODUCT	ARTICLE NUMBER / CONTENT	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
WAKOL Z 520 THIN SCREED, FIBRE REINFORCED 	<ul style="list-style-type: none"> • 159390 - 22 KG 	<ul style="list-style-type: none"> • Creates an even subfloor 3-40 mm • Gives the subfloor absorbent properties • Smooths out rough spot • Creates the preferred surface for gluing wood floors 	DRYING TIME: < 5 mm minimum 6 hours	1,8 kg/m ² /mm	
WAKOL Z 626 LEVELLING COMPOUND 	<ul style="list-style-type: none"> • 165660 - 22 KG 	<ul style="list-style-type: none"> • Creates an even subfloor 3-20 mm • Self flowing • Gives the subfloor absorbent properties • Smooths out rough spot • Creates the preferred surface for gluing wood floors 	DRYING TIME: < 5 mm minimum 6 hours	1,5 kg/m ² /mm	


MS ADHESIVES FOR SOLID WOOD & PARQUET FLOORS

PRODUCT	ARTICLE NUMBER / CONTENT	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
WAKOL MS 228 READY-TO-LAY, ELASTIC 	• 156680 - 18 KG	<ul style="list-style-type: none"> • For the installation of multi-layer parquet • Not in combination with WAKOL PU 280 Polyurethane Primer • Solvent and water free • Very good filling properties • 100% solid content • High initial grab • No known allergic reactions • Easy to remove from the floors and hands 	OPEN TIME: approx. 40 minutes	approx. 800-1500 g/m ² with trowel notch, approx. 1700-1800 g/m ² with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5	  
WAKOL MS 230, ELASTIC 	• 127532 - 18 KG	<p>For the installation of multi-layer parquet</p> <ul style="list-style-type: none"> • Solvent and water free • Very good filling properties • 100% solid content • High initial grab • No known allergic reactions • Easy to remove from the floors and hands 	OPEN TIME: approx. 40 minutes	approx. 700-1300 g/m ² with trowel notch, approx. 1700-1800 g/m ² with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5	  
WAKOL MS 260 FIRM-ELASTIC 	• 124504 - 18 KG	<ul style="list-style-type: none"> • For the installation of almost every wooden floor • Solvent and water free • Suitable for underfloorheating • Very good filling properties • 100% solid content • High initial grab • No known allergic reactions • Easy to remove from the floors and hands 	OPEN TIME: approx. 40 minutes	approx. 700-1500 g/m ² parquet approx. 400-450 g/m ² cork approx. 1700-1800 g/m ² with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5	  
WAKOL MS 262 FIRM-ELASTIC, SAUSAGE 	• 146521 - 600 cc	<ul style="list-style-type: none"> • Structure viscous • Solvent and water free • Very good filling properties • 100% solid content • Very high initial grab • No known allergic reactions • Easy to remove from the floors and hands 	OPEN TIME: approx. 40 minutes	approx. 450-500 ml/m ² combining with WAKOL TS 160/TS 170; approx. 600-800 ml/m ² strip application, approx. 500-950 ml/m ² with WAKOL Parquet Notched Trowel; approx. 425-850 ml/m ² WAKOL replaceable Nozzles	  

PU ADHESIVES FOR SOLID WOOD & PARQUET FLOORS

PRODUCT	ARTICLE NUMBER / CONTENT	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
WAKOL PU 225 ADHESIVE 	<ul style="list-style-type: none">• 124194 - 6,75 KG (A+B Compl)<hr/>• 122430 - 8,9 KG (A Compl)<hr/>• 122431 - 1,1 KG (B Compl)	<ul style="list-style-type: none">• Solvent and water free• Suitable for all types of wood flooring• Suitable for use with waterborne lacquers• Very good filling properties• 100% solid content• Excellent adhesion properties• Low emission level EC1	OPEN TIME: approx. 50 minutes	approx. 800- 1.500 g/m ²	

WATER BASED ADHESIVES FOR SOLID WOOD, CORK & PARQUET FLOORS

PRODUCT	ARTICLE NUMBER / CONTENT	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LECOL ADHESIVE PVAC					
	<ul style="list-style-type: none"> • 113333 - 0,75 KG • 122504 - 1 KG 	<ul style="list-style-type: none"> • Water resistant dispersion adhesive D3 • Joint adhesive for floating floors 	OPEN TIME: approx. 5-7 minutes		

WAKOL D 3540, CORK CONTACT ADHESIVE



- 100033 - 0,8 KG
- 100034 - 2,5 KG
- 100035 - 5 KG

Latex contact adhesive for laying cork tiles according to DIN EN 12104 with non-treated or treated surface on absorbent and non-absorbent subfloors. Also suitable for cork wall coverings and laying carpets on steps. WAKOL D 3540 corresponds to DIN EN 14259.

OPEN TIME:
approx. 120-180 minutes, with pre-coating approx. 60-90 minutes

Minimum 250 g/m² for laying cork, otherwise 150-650 g/m²



DPM IN ONLY 1 LAYER.

Applying a moisture suppressant is sometimes necessary if there is too much moisture in the subfloor and waiting is not an option. You can also opt for extra security and wait for the subfloor to dry naturally. In today's quick moving environment, this is the less likely option. With the WAKOL MS330 Silane Primer the waiting time is reduced to a minimum. You have a moisture barrier in just 1 layer and within 1 hour. As the product is completely free of epoxy and isocyanates it is also a cleaner choice for your project.

WHY CHOOSE WAKOL MS330 SILANE PRIMER?


- DPM in only 1 layer and dry within 1 hour!
- Free of epoxy and isocyanates, so much healthier to work with
- 1 component = no mixing, no pot life, no waste of material

PRODUCT APPLICATION.

- Consolidates the sub floor
- Binds old adhesive and plaster residues
- Isolates humidity in sand cement screeds, up to 95% KRL without UFH and 85% KRL with UFH
- After only 1 hour drying, direct installation of wooden floors can be started with a WAKOL MS Parquet Adhesive or
- After only 1 hour drying, self levelling can start with the appropriate WAKOL self levelling compound. Always apply the WAKOL D3045 Special Primer to the surface before the levelling compound is poured.



FLOW CHART WOOD FLOORING INSTALLATION UP TO 4 STEPS



- Identify Your Subfloor type & assess the risk of moisture present?
- Is a 'DPM' Chemical moisture suppressant required?
- Is the slab pre 1965? Can it be assumed there is no physical DPM?
- Have you performed a moisture test, using reliable and correct methods? (Hygrometer box)
- Are the moisture testing methods in accordance with British Standards 65% RH or below?
- Is the floor solid and stable, no decay, flaky paint, no movement, has laitance been removed?
- Concrete bases 150mm thick often take more than a year to dry from the face only!!

NO

Moisture is below 65% RH

Does the floor require levelling?

NO

YES



WAKOL D 3055
UNIVERSAL
PRIMER PARQUET



WAKOL D 3003 DISPERSION PRIMER



WAKOL Z 520 THIN SCREED,
FIBRE-REINFORCED



WAKOL Z 626
LEVELLING COMPOUND

SELECT THE ADHESIVE

Suitable for your chosen wood flooring product

SOLVENT



WAKOL MS 260 PARQUET ADHESIVE:
HIGH TENSILE STRENGTH &
WAKOL MS 262 PARQUET ADHESIVE



WAKOL PU 225
PARQUET ADHESIVE



LECOL 5500
ADHESIVE

wakol [®] | Anspruch verbindet

lecol [®]

FILLERS

PRODUCT	ARTICLE NUMBER / CONTENT	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LECOL FILLER 7500	<ul style="list-style-type: none"> • 156626 - 0,8 KG • 156555 - 5 KG 	<ul style="list-style-type: none"> • For the installation of multi-layer parquet • Not in combination with WAKOL PU 280 Polyurethane Primer • Solvent and water free • Very good filling properties • 100% solid content • High initial grab • No known allergic reactions • Easy to remove from the floors and hands 	DRYING TIME: approx. 30-60 minutes	100 ml	










LOBA EASYFILL




















<ul style="list-style-type: none"> • 146029 - 5 L 	<ul style="list-style-type: none"> • Waterbased binder. • Easy to work with • Closes even wider joints by one-time application • No subsiding of the filler in the joint • Very fast drying Excellent sandability; clearly visible and low adhesion on sanding paper • Excellent color scheme for oiled and finished surfaces • Applicable to all common European and exotic wood types • Odour neutral 	DRYING TIME: approx. 15 - 30 minutes	100 ml	
--	---	---	--------	--

LACQUERS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LOBA EASYPRIME 	<ul style="list-style-type: none"> • 133523 - 5 L 	<p>Polyurethane-acrylate waterbased primer for roller and trowel application for wooden floors.</p> <ul style="list-style-type: none"> • Used on millions of m² worldwide every year • All-rounder offering maximum processing reliability • No roller marks • Premium quality at a fair price • Optimised adhesion between wood and finish • Reduces side bonding • Suitable for use with practically all European and exotic woods, as well as in sports and multipurpose halls 	<p>DRYING TIME: 60 minutes</p>	100 ml	
LOBA PRIMASEAL PLUS 	<ul style="list-style-type: none"> • 156556- 5 L 	<p>Alcohol-based primer for wooden floors</p> <ul style="list-style-type: none"> • Excellent flow properties • No roller marks • Beautiful deep natural colour • Suitable for all wooden floors (universally applicable) • No mixing • Quick drying • Low solvent • No odours • Good price-performance ratio 	<p>DRYING TIME: 40-60 minutes</p>	100 - 120 ml	
LOBA 2K INVISIBLE PROTECT 	<ul style="list-style-type: none"> • 137273 - 1 KG • 137274 - 5 KG 	<p>Waterbased surface protection for parquet and hardwood floors.</p> <ul style="list-style-type: none"> • This lacquer combines the looks of an oiled surface with the protection and ease of maintenance of a water based lacquer. • Natural structure and feel like untreated wooden flooring • Extremely easy to work with • 2-layer full structure without priming • Increased anti-slip properties • No additional polishing required • Excellent chemical resistance • As easy to clean as finished surfaces • No grain accentuation, the original colour of the wood remains as it was in its original state 	<p>DRYING TIME: 4-6 hours</p>	100 - 130 ml	
LOBA 2K SUPRA A.T. 	<ul style="list-style-type: none"> • 123946- 5 KG Semi Gloss • 135511- 5 KG Matt 	<p>Ceramic-reinforced waterbased 2-component polyurethane finish for wooden floors.</p> <ul style="list-style-type: none"> • Fully usable after 24 hours • Sets new standards in quality • Meets highest demands • Extremely high scratch resistance thanks to ceramic components • Qualified for various floorings 	<p>DRYING TIME: 4-6 hours</p>	100 - 120 ml	

LACQUERS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LOBA 2K DUO 	<ul style="list-style-type: none"> • 165877 - 5 KG Matt • 123946 - 5 KG Semi Gloss 	<p>Waterbased 2-component polyurethane finish for wooden floors.</p> <ul style="list-style-type: none"> • Easy and safe application • Excellent wear resistance • Certified anti-slip properties as per BGR 181 for work areas • Available in matt and gloss 	<p>DRYING TIME: 4-6 hours</p>	100 ml	 
LOBA 2K FUSION 	<ul style="list-style-type: none"> • 133521 - 5 KG Matt • 135501 - 5 KG Semi Gloss 	<p>Waterbased 2-component polyurethane finish for wooden floors.</p> <ul style="list-style-type: none"> • Easy and safe application • Excellent wear resistance • Good price/performance ratio • Certified anti-slip properties as per BGR 181 for work areas • Available in matt and semi gloss 	<p>DRYING TIME: 4-6 hours</p>	100 - 120 ml	 
LOBA EASYFINISH 	<ul style="list-style-type: none"> • 135509 - 1 L Matt • 135503 - 5 L Matt • 135505 - 5 L Semi Gloss 	<p>Waterbased 1-component finish for wooden floors.</p> <ul style="list-style-type: none"> • Easy 1K system combined with 2K performance • Outstanding application qualities – easy to use and safe, no lap marks • Very low emission, certified to EMICODE® EC1 • Suitable for almost all wood species as well as cork • EasyFinish semi-gloss combined with LOBA SportCare meets the requirements for friction according to DIN 18032 for sports floors • Long-lasting beauty of the floor – high resistance to mechanical wear and household chemicals 	<p>DRYING TIME: 4-6 hours</p>	100 - 120 ml	 
LOBA VIVA 	<ul style="list-style-type: none"> • 150088 - 5 L Matt • 150087 - 5 L Semi Gloss 	<p>Waterbased 1-component finish for wooden floors.</p> <ul style="list-style-type: none"> • Excellent chemical and abrasion resistance • Very good resistance to black heel marks • Powerful resistance to plasticisers from parquet adhesives • Easy and safe application, no lap marks • Full "Connected Systems" approval • Low VOC content • Very low emission, certified to EMICODE® EC1 • Available in matt and semi gloss 	<p>DRYING TIME: 4-6 hours</p>	100 - 120 ml	 

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LOBA LIFE					
	• 167879 - 5 L Semi Gloss	Waterbased 1-component finish for wooden floors. <ul style="list-style-type: none"> • Good price/performance ratio • Balanced properties • High filling capacity • Easy and safe application 	DRYING TIME: 4-6 hours	100 - 120 ml	
LOBA WHITENER					
	• 149780 - 80 ML	Waterbased 2-component polyurethane finish for wooden floors. <ul style="list-style-type: none"> • Easy and safe application • Excellent wear resistance • Good price/performance ratio • Certified anti-slip properties as per BGR 181 for work areas • Available in matt and semi gloss 		100 - 120 ml	
LOBA AMBERIZER					
	• 150735 - 100 ML	Additive to achieve a color intensification of wood surfaces. <ul style="list-style-type: none"> • May be combined with all waterbased primers and finishes from LOBA • For an aged look with the resistance of a finished surface • Adjustment of newly finished surfaces to solvent-containing finished existing surfaces • Waterbased technology, solvent-free • Simple and safe application 		100 - 120 ml	
LOBA SLIP RESIST					
	• 167624 - 100 ML	Water-based additive for creating a slip-preventing surface of evaluation group R10 on various types of flooring. It's for water-based LOBA sealing products in Matt versions & can be combined with other LOBA Additives. <ul style="list-style-type: none"> • Certified slip resistance • Solvent free • Simple & safe application • Simplified storage 		100 gr -5 L	

SOLVENT COLOURS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
---------	----------------------------------	-------------	--------------------	------------------	--------------

LOBA STAIN



750 ML
See all article numbers & colours below.

Stain is a solvent-based stain for hardwood flooring. Especially created for those who want to pick up the pace.

- Solvent based
- Reduces the side bonding tendency of water-based finishes
- Easy application
- Fade resistant through the use of special pigments
- Soft grain of the wood does not become darker
- Excellent coverage
- Compatible with all LOBA water-based finishes

DRYING TIME:
2 hours

45-60 ml

Available in 12 deep colours

STAIN COLOURS

COLOUR	NAME	ARTICLE NUMBER	CONTENT	COLOUR	NAME	ARTICLE NUMBER	CONTENT
	Classic Grey	167898 170061	750ml 100ml		Nutmeg	170049 170069	750ml 100ml
	Country White	170050 170093	750ml 100ml		Provincial	168917 170091	750ml 100ml
	Dark Grey	170010 170063	750ml 100ml		Walnut	167900 170068	750ml 100ml
	Ebony	167899 170092	750ml 100ml				
	Golden Oak	168919 170071	750ml 100ml				
	Heritage Brown	170012 170065	750ml 100ml				
	Jacobean	168916 170070	750ml 100ml				
	Mahagony	170011 170064	750ml 100ml				
	Medium Brown	170048 170067	750ml 100ml				



SOLVENT BASED ADHESIVES FOR SOLID WOOD & PARQUET FLOORS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFI- CATES
---------	-------------------------------------	-------------	-----------------------	---------------------	-------------------

LECOL ADHESIVE 5500



- 156558 - 6 KG

- 156554 - 16 KG

- 156557 - 25 KG

- High initial grab
- Suitable for all types of wooden flooring
- Very good filling properties
- Water Free

OPEN TIME:
approx. 5-10
minutes

Consumption
/ m2
700-900 g/m²

ULTIMATE PROTECTION, INVISIBLY.

LOBA 2K INVISIBLE PROTECT. Latest-generation, waterborne surface protection for parquet and hardwood floors. For extremely heavy wear. The natural look and feel of the untreated wood is maintained. The virtually invisible layer is also extremely scratch-resistant thanks to the use of the highest-quality raw materials. elastic, excellent chemical and abrasion resistance.

- Natural structure and feel like untreated wooden flooring
- 2 coat system without primer
- Certified non-slip properties as per BGR 181 for work areas
- No polishing effect
- Excellent chemical resistance
- As easy to clean as finished surfaces
- No grain accentuation, the original colour of the wood remains as it was in its original state



ADDITIVE FOR BRIGHTENING WOOD SURFACES

LOBA Whitener is an additive that can be added for a smooth brightening of wood floors. The intensity of the whitening may be individually controlled by variable application in one or more layers.





lecol[®]

HARD WAX OILS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LOBA HARDWAX OIL MATT 	• 169978 - 750ML	<p>High-quality, layer-forming hard wax oil accentuating the natural look of the wood and at the same time achieve excellent resistance to dirt and water.</p> <ul style="list-style-type: none"> • Resistant against abrasion • Repels dirt and water • Suitable for partial repairs • Natural, velvety feel • Water and dirt resistant • Easy and safe application • Certified anti-slip class R10. • Suitable for children's toys as per DIN EN 71-3 	<p>DRYING TIME: 8 hours</p>	60-80ml (roller)	

LOBA HARDWAX OIL NATURE

	• 169979 - 750ML	<p>High-quality, layer-forming hard wax oil that preserves the natural beauty and feel of untreated raw wood. It's durable, slip resistant and protects against dirt and water.</p> <ul style="list-style-type: none"> • Resistant against abrasion • Repels dirt and water • Suitable for partial repairs • Natural, velvety feel • Dirt resistant, easy to clean surface • Easy and safe application • Certified anti-slip class R10. • Suitable for children's toys as per DIN EN 71-3 	<p>DRYING TIME: 8 hours</p>	60-80ml (roller)	
--	------------------	---	---------------------------------	------------------	---

OIL & COLOURS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
---------	----------------------------------	-------------	--------------------	------------------	--------------

LOBA PRETONE



2,5 L
See all article numbers & colours below.

Waterborne pigment stain for intensifying the colour under coloured oils

- Water based stain
- In combination with LOBA 2K ImpactOil
- For beautiful deep colour effects
- 5 colours available
- Solvent free

PRETONE COLOURS

COLOUR	NAME	ARTICLE NUMBER	CONTENT
	White	137310	2,5 L
	Brown	139737	2,5 L
	Black	139736	2,5 L
	Mocha	146830	2,5 L
	Steel	146831	2,5 L

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
---------	----------------------------------	-------------	--------------------	------------------	--------------

LOBA IMPACTOIL COLOR



See all article numbers, sizes & colours below.

Natural flooring oil for high quality demands in different colours. Accentuates the natural character of the wood and achieves excellent properties.

- One coat impregnation
- Transparent and 11 colours
- Natural finish
- Simple and safe application
- Excellent water resistance for parquet flooring in wet zones such as bathrooms or spa areas
- Time-saving processing in a 1-day system
- Extremely economical to use
- 100% solid – solvent-free
- Certified anti-slip properties as per BGR 181 for work areas
- Easy and safe application
- One roller application is sufficient
- Can be used after only 24 hours
- Suitable for children’s toys as per DIN EN 71-3

DRYING TIME:
12 hours





60 gr







IMPACTOIL COLOURS

COLOUR	NAME	ARTICLE NUMBER	CONTENT	COLOUR	NAME	ARTICLE NUMBER	CONTENT
	Transparent	123446	750 ml		Papyrus	123464	750 ml
		122298	2,5 KG				
	Antique Oak	134358	750 ml		Sand	134353	750 ml
		167939	100 ml			167945	100 ml
	Black	134357	750 ml		Silver	134355	750 ml
		167940	100 ml			167946	100 ml
	Chalk	134357	750 ml		Smoked Oak	125107	750 ml
		167941	100 ml			167947	100 ml
	Clay	134352	750 ml		Sucupira	125102	750 ml
		167942	100 ml			167948	100 ml
	Grey	134356	750 ml		Wenge	125108	750 ml
		167945	100 ml			167950	100 ml




MAINTENANCE PRODUCTS

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LOBA REFRESH					
	• 138697 - 1 L	<p>Waterbased wipe care product for floors treated with LOBA 2K InvisibleProtect.</p> <ul style="list-style-type: none"> • Can be used universally on various finished floors • Extremely economical concentrate • Can also be machine applied • Clearly visible care effect • No basic cleaning required 	n.a.	n.a.	
LOBA CLEANER					
	• 156684 - 1 L	<p>Day-to-day cleaning for lacquered and oiled floors. Highly concentrated, pH-neutral cleaner.</p> <ul style="list-style-type: none"> • Excellent cleaning effect thanks to superb dirt-dissolving power • Extremely economical concentrate, 1 litre of LOBACARE Cleaner yields up to 200 litres of ready-to-use cleaning solution • Material-protecting and pH-neutral • Can be used universally for all waterproof surfaces • Environmentally friendly biodegradable cleaner 	n.a.	n.a.	
LOBA CAREREMOVER					
	• 161695 - 1L	<p>Deep cleaning for lacquered floors. Remover for finished floors.</p> <ul style="list-style-type: none"> • Removes old layers of care product • Removes stubborn dirt • Can be used universally on various finished floors • Material-protecting and pH-neutral 	n.a.	n.a.	
LOBA PERMANENT CARE					
	• 167951 - 1L Matt • 167951 - 1L Gloss	<p>Maintenance for lacquered floors. Polyurethane floor care product.</p> <ul style="list-style-type: none"> • Particularly wear-resistant, pure PU permanent care product • Provides long-term protection against wear • Brings new shine to heavily used and worn floors • Can be used universally on various finished floors • Extremely high scuff-mark resistance 	n.a.	n.a.	

PRODUCT	ARTICLE NUMBER / CONTENT / GLOSS	DESCRIPTION	OPEN / DRYING TIME	CONSUMPTION / M2	CERTIFICATES
LOBA SPORTCARE					
	• 168913 - 1L	<p>Maintenance for lacquered sport floors Waterbased floor care product.</p> <ul style="list-style-type: none"> • Maintains the floor's value and appearance • Provides long-term protection against wear • Brings new shine to heavily used and worn floors • Prevents scuff marks from shoe soles in the finish • Especially safe to walk on • Easy and safe application 	n.a.	n.a.	
LOBA PARKETTCARE					
	• 150171 - 1L	<p>Maintenance for lacquered floors Waterbased floor care product.</p> <ul style="list-style-type: none"> • Maintains the floor's value and appearance • Provides long-term protection against wear • Can be used without restriction for prefinished wood floors • Recommended by leading industrial wood floor manufacturers • Brings new shine to heavily used and worn floors • Easy and safe application 	n.a.	n.a.	
LOBA PARKETTOIL					
	• 156683 - 1L	<p>Maintenance oil solvent-based for oiled floors.</p> <ul style="list-style-type: none"> • Refreshes tired and worn floors • Removes slight damage in oiled surfaces • Ideal for full-surface care or partial improvements • Easy and safe application • Preserves the anti-slip properties of oiled flooring 	n.a.	n.a.	
LOBA PARKETTSOAP					
	• 156682 - 1L	<p>Day-to-day cleaning for oiled and waxed floors Waterbased soap for oiled and waxed floorings.</p> <ul style="list-style-type: none"> • Good cleaning effect • Care effect 	n.a.	n.a.	

INSTALLATION ACCESSORIES/ANCILIARIES

	PRODUCT	ARTICLE NUMBER	DESCRIPTION	CONTENT
	ADHESIVE TROWEL WAKOL B11	144006		1 piece
	WAKOL AR150 REINFORCEMENT FABRIC	124209	Fibreglass fabric for reinforcing levelling compounds on inhomogeneous subfloors, wood planks and wood product tile subfloors as well as in sports facility construction in systems with WAKOL D 3060 Plastification Additive and Wakol levelling compound.	50 M2
	WAKOL R4515 TILE CLEANER	121365	Cleaner for manual or machine application on old tiled floors for removal of layers of old care products and extreme dirt before subsequent laying.	5L
	WAKOL TS102 SOUNDPROOFING MAT (2MM)	132993	Cork/polyurethane foam matting for improving the footfall soundproofing and heat insulation of flooring structures in old and new buildings. WAKOL TS 102 is suitable as soundproofing material under PVC, CV, textile, linoleum and caoutchouc flooring, as well as mosaic parquet (cubes), on edge lamella, strip, multi-layer parquet, wood block RE/WE, solid wood planks (type of wood oak, max. 16 cm in width) and stratified flooring indoors.	30 M2
	WAKOL TS160 SLATTED UNDERLAY	124208	Polypropylene soundproofing mat with single-sided aluminium lamination for improving the footfall sound insulation. WAKOL TS 160 Footfall Soundproofing Mat has cut-outs for accommodating WAKOL MS 262 Parquet Adhesive, firm-elastic, and is suitable for laying strip parquet and solid wood planks up to max. 18 cm in width and multi-layer parquet as of 90 cm in length indoors.	15 M2
	WAKOL MEASURING BUCKET (+ LID)	127473		11 KG

	PRODUCT	ARTICLE NUMBER	DESCRIPTION	CONTENT
	WAKOL MIXING BUCKET	100835		30L
	MANUAL BULK GUN	163522		1 piece
	LOBA ROLLER FOR WATER-BASED LACQUERS	100509		1 piece
	LOBA BUCKET FOR LACQUERS	100830		1 piece
	LOBA MIXING JUG FOR LACQUERS	101106		1 piece
	LOBA INLINER BAGS	100831		25 pieces
	LOBA SPRAY MOP	138808	Practical mop with integrated spray system specially developed for the cleaning of parquet, hardwood and cork floors. Fast and easy cleaning, no bucket required.	1 set
	LOBA SPRAY MOP COVER	138811	Microfibre mop cover for LOBAHOME SprayMop and Mop. Washable at 60°C.	1 single cloth



Alex Jeakins

T +44 (0)7496282829 // E alexjeakins@lecoluk.com

Duncan Conlan

T +44 (0)7534941817 // E duncanconlan@lecoluk.com

Fraser McArthur

T +44 (0)7956134481 // E frasermcarthur@lecoluk.com

Lecol UK // www.lecoluk.com // sales@lecoluk.com

