

PrimaSeal Plus



PRIMER



Alcohol-based primer for wooden floors.

- Easy and safe application
- Excellent blocking of wood ingredients and old contamination
- Intensifies the color of the wood
- Good price/performance ratio

Range of use:

Suitable for virtually all types of European and exotic timber. Note the LOBA wood types list, which can be found at www.loba.de. If in doubt, consult the factory. The side-bonding effect of Water-based finishes is reduced. No block bonding occurs with parquet or wooden flooring that has been properly laid and bonded or secured with shear-resistant adhesive.

Technical Data

ART.-NO.			
11033	5l	4	128

Storage and transportation
GISCODE

18 months of storage stability.
 Not sensitive to frost.
 G1

Application

- The surface must be professionally sanded. The floor must be dry and free of any old coatings, oil, grease, wax, silicone, sanding dust and other impurities.
- The optimal processing conditions are room temperature +15°C to +25°C, floor temperature +15°C to +22°C, rel. humidity 40% to 75%, material temperature +18°C to +25°C, max. wood moisture 12%, sufficiently ventilate working rooms.
- In order to prevent parquet damage, the room temperature should be set to the annual average expected for the use of the product.
- To reduce the risk of excessive swelling, we recommend applying a maximum of 2 roll applications per day.
- Transfer material to a LOBA varnish bucket before applying.
- Stir the material well.
- Observe general and, if necessary, product-specific occupational health and safety regulations. Further information can be found in the GISCODE-related operating instructions which are available under www.wingis-online.de.

THINNER / MIXING

The product is ready for use and must not be reduced!

APPLICATION TOOL / APPLICATION RATE

LOBA roller Universal 100 / 100 - 120 ml/m² (8-10 m²/l).

INTERMEDIATE SANDING

Do not intermediate-sand the primer.

DRYING TIME

- Do not varnish over before approx. 60 minutes have elapsed.
- If there are drying delays, wait until completely dry.

SUITABLE FINISHES:

- Normal traffic:**
- Life.

Application

Up to heavy traffic:

- EasyFinish.
- Viva.

Up to very heavy traffic:

- 2K Supra A.T..
- 2K Duo.
- 2K Fusion

APPLICATION FOR PARQUET AND WOODEN FLOORING:

- Prepare the substrate properly.
- Roller on the primer generously.
- Drying.
- Roll on LOBA Water-based finish.

General guidelines

Cleaning of tools: Clean tools with solvents such as brush cleaner.

Drying time: The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

Safety notes: Flammable solvent vapours emerge during the drying process when working with products containing high quantities of solvents. As a result, fire, naked light, welding, smoking and so on are prohibited in the immediate vicinity of such products. Ventilate working areas and storage rooms well. Electrical equipment in workrooms and ancillary rooms must be switched off in sufficient time to ensure that they are cold when work begins. Any spark generation, including on electrical equipment, must be avoided. Keep material containers tightly closed. Solvent sensitive components, plants or animals (fish tanks) must be removed from areas at risk of exposure to solvent vapours.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.